


Distributed by Lightweight Manufacturing

1139 Sumner Ave  
Whitehall, PA 18052  
T 610-435-4720  
F 610-465-8866  
Email: Sales@kedermakerusa.com  
Web: www.kedermakerusa.com



All Kedermaker styles listed are inventory items

Keder style	Color	Diameter (mm)	Weld Size (mm)	Fabric Style	Fabric Weight (g/m2)	Flag style	Flag Width (mm)	Roll Length (M)
MS4-5-12W	White Trans	3.5	5	Plain Weave	400	single	12	200
MS4-5-12B	Black	3.8	5	Plain Weave	400	single	12	200
MD4-5-15	Black	3.8	5	Plain Weave	400	double	18	200
AS5-10-30	White Trans	5	5	Plain Weave	460	single	30	200
AS(7)-8-20	White trans	7	8	Plain weave	460	single	20	200
AS(7)-8-25	White trans	7	8	Plain weave	460	single	25	200
AS(7)-8-30	White trans	7	8	Plain weave	460	single	30	200
GD(7)-10-30	White opaque	7	10	Panama	750	double	30	200
GS(8)-10-30	White opaque	8	10	Panama	750	single	30	200
AS(8)-10-30	White trans	8	10	Plain weave	460	single	30	200
GD(8)-10-30	White opaque	8	10	Panama	750	double	30	200
HD(8.5)-10-30	Black	8.5	10	Panama	750	double	30	200
CS(11)-20-30	White trans	11	20	Panama	750	single	30	200
GD(11)-10-30	White opaque	11	10	Panama	750	double	30	200
PD(13)-10-30	White opaque	13	10	Panama	900	double	30	200
GS(13)-20-30	White opaque	13	20	Panama	750	single	30	200
HD(13)-10-30	Black	13	10	Panama	750	double	30	200

Renew Keder	Color	Diameter (mm)	Weld + Flag (mm)	Fabric Style	Fabric Weight (g/m2)	Flag Style	Strip Width (mm)	Roll Length (M)
Renew keder 8mm	White opaque	8	40	Panama/XYD	900	overlapping	25	200
Renew keder 11mm	White opaque	11	40	Panama/XYD	900	overlapping	25	200
New Renew Keder 13mm	White opaque	13	40	Panama/XYD	900	overlapping	25	200

Renew keder: standard PD13-10-30 with white opaque coated fabric strip extending 1 inch / 25mm, to repair existing keder panels that used keder with 10mm weld, 30mm flag.

Kedercord weld: Kedermaker welds the keder fabric to the extruded kedercord. This welded connection prevents the kedercord from separating in the fabric pocket and it provides better integrity of the keder connection when the keder is damaged. For every production batch this weld between kedercord and fabric is tested to make sure it meets minimum strength requirements.

The P style keder has twisted yarns to decrease fraying at the edges, and has anti-wicking threads to reduce absorption of moisture.

Panama Weaving: A weaving pattern based on weaving 2 threads in each direction creating a stronger fabric with the same thread weight since more threads can be woven per unit of width. The weave is not as tight as in a plain weave, but stronger and heavier.

Other sizes available – please contact us for pricing, minimum quantities and leadtimes

First letter of product code = Fabric Style

Second letter of product code = S(single) or D(Double) flag

Number in parentheses, ex. (13) = Diameter; -10-30 = 10mm weld and 30mm flag